

# Model MERCURY S

## Technical Data

Operating voltage:	85...264VAC /50...60Hz
Standby:	18 Watts / 80 mA
Rated Power:	91 Watts / 400 mA (max.)
Dimensions (incl. format slide unit):	1110 (max.) x 450 x 365 mm (l x w x h)
Weight:	32.1 kg
Piling-Option (for stacked and nested envelopes!):	standard
Automatic Start/Stop:	optional (Models MERCURY SIR/SIRC)
Counter (integrated):	optional (Models MERCURY SC/SIRC)
Length of receiving tray:	400 mm
Max. width of envelope:	335 mm (B5/B4, C6/5, C4, C4 Pocket)
Max. thickness of package:	6 mm
Max. sealing capacity (C5, C5/6):	18'000 envelopes per hour
Power cable length:	2.0 meters (external)
Area of use:	according to EU-Norms
Licensing:	CE
Product warranty:	2 years
Accessories (incl.):	Cover, suction rubber pear, replacement fuse, instruction manual

In the interest of further technical development, any design and technical modifications to the Envelope Sealing Machine are reserved.



### MAAG MERCURE LTD

Envelope Sealing Machines

Webereistrasse 59

CH-8134 Adliswil

Tel. +41 (0)44 710 40 41

info@maag-mercure.ch

www.maag-mercure.ch