

Model TAURUS

Technical Data

Operating voltage:	85...264VAC / 50Hz...60Hz
Standby:	18 Watts / 80 mA
Rated Power:	91 Watts / 400 mA (max.)
Dimensions (incl. format slide unit):	1110 (max.) x 370 x 370 mm (l x w x h)
Weight:	25.6 kg
Piling-Option:	standard (for stacked and nested envelopes!)
Automatic Start/Stop:	standard on models TAURUS IR/IRC
Counter (integrated):	standard on models TAURUS C/IRC
Length of receiving tray:	382 mm (standard)
Max. width of envelope :	250 mm (B5/B4, B6/5)
Max. thickness of package*:	16 mm
Max. sealing capacity (C5, C5/6):	18'000 envelopes per hour
Power cable length (fixed):	2 meters
Area of use:	according to EU-Norms
Licensing:	CE
Product warranty:	2 years
Accessories (incl.):	Cover, suction rubber pear, replacement fuse, instruction manual

* Position of basin two-stage adjustable for envelopes from 0...8mm and 8...16mm. The contents of the envelope in the case of letter thicknesses > 8 mm must be homogeneous, i.e. the max. deviation within the envelope may not exceed 1 mm. Folded letters should be folded as flat as possible!

In the interest of further technical development, any design and technical modifications to the Envelope Sealing Machine are reserved.



MAAG MERCURE AG

Mail Processing Machines
Webereistrasse 59
CH-8134 Adliswil
Tel. +41 (0)44 710 40 41
info@maag-mercure.ch
www.maag-mercure.swiss